



ZODIAC[®]
a better life[®]

SALT CHLORINATOR



PROGRAMMABLE
AND LONG LASTING

Ei² Expert

1 EXTREME DURABILITY

One of the **longest-lasting** chlorinators in its category thanks to its **high quality titanium** electrode (operates for up to 10,000 hours).

Ti²²
TITANIUM
INSIDE

2 SUITABLE FOR ALL INSTALLATIONS

The compact cell and watertight IPX5 casing enable the Ei² Expert to be installed anywhere, **in confined spaces and even in humid environments.**


EASY
INSTALLATION

3 CONTROLLED CHLORINE PRODUCTION

Ei² Expert offers **4 operating modes** and a programming clock **enabling you to perfectly control the production of chloride according to the season or pool use.**


CHLORINE

SPECIFICATIONS



Quick and easy to install

Thanks to its patented Quick Fix cell.



No maintenance

Self-cleaning electrodes via reverse polarity.

STOP

Safe system

Automatic stop if there is no flow in the cell.



Waterproof

Water-resistant 'IPX5-rated' control unit.



Unconditional guarantee

On the control box and the cell, whatever the causes of damage.

FOR WHICH TYPE OF POOLS?

1 ALL TYPES OF SWIMMING POOLS



2 POOLS UP TO 110M³
(TEMPERATE CLIMATE,
FILTRATION 8 HR/DAY)



STANDARD FEATURES



Cell installation kit



Installation kit for flow detector

TECHNICAL INFORMATION

MODELS	Ei ² Expert 10	Ei ² Expert 18	Ei ² Expert 25
Volume of water treated (temperate climate, filtration 8hr/day)	40 m ³	70 m ³	110 m ³
Nominal chlorine production	10 g/hr	18 g/hr	25 g/hr
Power rating	60 W	100 W	140 W
User Interface	Multilingual, backlit LCD screen		
Operating modes	Summer, Winter, Boost (100%), Low (shutter mode 10%)		
Clock/Timer	24 hr clock / 2 timers		
Reverse polarity	Yes: 3, 5 or 7 hr (factory settings = 5 hr)		
Recommended salt level - minimum	4 g/L - 3.0 g/L minimum (*)		
Safety features	'Low salt' indicator message: reduced production to protect the electrode 'No flow' indicator message: production is interrupted until optimal conditions return		
Cell position	Horizontal or vertical		
Compatible pipework	DN50, DN63, 1½" (48 mm)		
Protection rating	IPX5		
50 Hz power supply	220-240 VAC (mains power cable with moulded plug)		

AVAILABLE ACCESSORIES



Locking ring wrench



Winterizing cap

Salt chlorinators are an **automatic and efficient** disinfection solution. **They are easy to use**, offer complete water treatment and **reduce maintenance**.

2 YEAR
WARRANTY